

Product Specifications

FlashLink® NOW 4G Real-Time In-Transit Logger

Temperature Range	-30°C to 55°C (-22°F to 131°F)
Temperature Accuracy	±0.5°C from -10°C to 40°C (±0.9°F from 14°F to 104°F) ±1.0°C (°2.0°F) Other
Temperature Resolution	0.1°C/°F
Sensor Type	Internal Digital Temperature Sensor
Temperature Scale	Dual-scale °F/°C (Default °F)
Light Detector	0-20 Lx
Usage Type	Single Use
Data Capacity	Max 27000 readings
Logging Interval	20 Min.
Data Upload Interval	120 Min.
Trip Duration	Up to 70 days in Ocean Mode at -5°C to 55°C (23°F to 131°F)
Communication	Global 4G/5G network, with 2G Fallback
SIM	Internal Embedded Nano Sim (Global Data Roaming)
Power Source	Non-Lithium Battery [Alkaline]
Battery Shelf Life	12 months
Logger Dimensions	4.2in [with loop: 4.5in] x 2.7in x 0.9in (106.4mm [with loop: 113.8mm] x 68.6mm x 22.3mm)
Weight	6.14 oz (174 grams)
Waterproof Rating	IP66
Certification	FCC, CE, ROHS, TELEC, NIST, WEEE, ISO17025 (optional)
PDF Report Backup	Download full trip PDF report via USB-C



Model 23008

- Equipped with global network communication compatibility and precision location accuracy through Wi-Fi triangulation positioning
- Monitors and provides alerts for in-transit real-time location, temperature, and light
- A unified cloud platform connecting cold chain IoT devices and applications, with seamless integration, automation, built-in analytics and business intelligence.
- Easily switch between °F and °C on the LCD display upon activation

SS 23008_26D3

